

UNCLASSIFIED

AD NUMBER
AD458510
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; 23 FEB 1965. Other requests shall be referred to US Army Coating and Chemical Laboratory, Aberdeen Proving Ground, MD 21010.
AUTHORITY
USACCL ltr, 17 Dec 1965

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD_ 4 5 8 5 1 0

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION


CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

4 5 8 5 1 0



AD

CATALOGED BY DDC
AS AD No. 458510


CCL REPORT NO. 176

STORAGE STABILITY OF BRAKE FLUIDS

FINAL REPORT

BY

C. B. JORDAN
23 FEBRUARY 1965



AMCMS CODE NO. 5025.11.802
DA PROJECT IC024401A108

U. S. ARMY COATING & CHEMICAL LABORATORY

Aberdeen Proving Ground
Maryland

DDC AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from Defense Documentation Center, Cameron Station, Alexandria, Virginia 22314.

THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF THE ARMY POSITION, UNLESS SO DESIGNATED BY OTHER AUTHORIZED DOCUMENTS.

DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED. DO NOT RETURN IT TO THE ORIGINATOR.

UNCLASSIFIED

CCL REPORT NO. 176

STORAGE STABILITY OF BRAKE FLUIDS

BY

C. B. JORDAN

23 FEBRUARY 1965

AMCMS CODE NO. 5025.11.802

DEPARTMENT OF THE ARMY PROJECT NO.
1C024401A108

U. S. ARMY COATING AND CHEMICAL LABORATORY
ABERDEEN PROVING GROUND
MARYLAND

UNCLASSIFIED

ABSTRACT

The object of this study was to investigate the stability of corrosion inhibiting systems found in brake fluids approved under Federal Specification VV-H-910a after extended storage of the fluids in steel and glass containers.

Corrosion and oxidation stability tests outlined in VV-H-910a were conducted on twenty-two approved fluids after $2\frac{1}{2}$ years storage in 5-gallon steel containers and on eight approved fluids after 5 years storage in 1-gallon glass containers.

In all tests conducted there was evidence of inhibitor instability or depletion. Sixteen of the twenty-two fluids stored in cans and five of the eight fluids stored in glass failed to meet minimum requirements of specification VV-H-910a. Nine of the fluids stored in cans and three of the fluids stored in glass also fail the more relaxed requirements of Society of Automotive Engineers Specification, 70R1, which is the controlling specification of the Federal Register.

TABLE OF CONTENTS

	<u>Page No.</u>
TITLE PAGE	i
ABSTRACT	ii
INTRODUCTION	1
DETAILS OF TEST	1
RESULTS OF TEST	1 - 2
DISCUSSION	2 - 3
REFERENCES	3
DISTRIBUTION LIST	4 - 5
APPENDIX	6
Tables	6 - 8
DD FORM 1473	9

I. INTRODUCTION

The U.S. Army Coating and Chemical Laboratory, Aberdeen Proving Ground, Maryland, was authorized by AMC Directive, AMC Code 5025.11.802, dated 24 July 1964 to conduct research on hydraulic brake fluids.

One area of investigation concerned the effectiveness of corrosion inhibitor systems of brake fluids after prolonged storage in containers. Experience had indicated that sometimes the inhibitors were chemically unstable and were rendered ineffective by the interreaction of the chemicals which composed the inhibitor formulation. This was evidenced by the formation of precipitates or sediment in cans of stored brake fluids. It was believed that inhibitor depletion may also occur in other instances not visually evident. In order to determine if this was the case, corrosion and stability tests were conducted on brake fluids which had been approved under Federal Specification VV-H-910 and stored in their original steel containers for 2½ years and in glass bottles for 5 years. This report contains the results of these tests.

II. DETAILS OF TEST

A. Brake Fluids Tested

Series 1 - Twenty-two fluids which had been approved under Federal Specification VV-H-910a were tested. These fluids had been in storage in an unheated warehouse in their original 5-gallon steel containers for 30 months. Each can contained approximately 2 to 3 gallons of fluid. Eight different brake fluid manufacturers were represented in this series of tests.

Series 2 - Tests were conducted on eight of the above fluids which had been stored in glass bottles at room temperature for five years. Six different manufacturers were represented in this series of tests.

B. Tests Conducted

a. Corrosion test - All fluids were subjected to the corrosiveness test specified in paragraph 4.5.11 of Federal Specification VV-H-910a. This test consists of the immersion of a set of six different metals (in electrolytic contact) in the fluid being tested, and heating at 210°F. for 120 hours. Weight loss of the metal specimens is measured and visual evidence of corrosion is noted.

b. Stability test - All fluids were subjected to the stability test specified in paragraph 4.5.14 of Federal Specification VV-H-910a. This test consists of the partial immersion of a set of aluminum and cast iron test specimens (electrolytically coupled) in a sample of the fluid to be tested. 0.2% Benzoyl Peroxide and 5% water is dissolved in the fluid. The test specimens are immersed for 3 days at room temperature and for 7 days at 158°, after which weight loss is calculated and visual evidence of corrosion noted.

III. RESULTS OF TESTS

Fourteen of the twenty-two brake fluids in Series 1 failed to meet the

Best Available Copy

minimum requirements of WV-H-910a in the corrosion test. Ten of the fluids failed the oxidation stability test.

Four of the eight fluids in Series 2 failed the corrosion test and four failed the stability test.

Nine of the fluids stored in cans and three of the fluids stored in glass also be judged to fail the more relaxed requirements of Society of Automotive Engineers Specification 70R1, which is the controlling specification of the Federal Register.

A comparison of test results with the results received at the time the fluids were originally qualified showed that in nearly every test there was evidence of inhibitor depletion upon storage, even though several of the fluids still met the minimum requirements of the specifications.

It is of interest to note that five of these fluids were placed in systems simulating standby storage. Four failed after one year's storage and one passed. All four fluids failing the standby storage test also fail in this storage test and the one which passed in standby storage was satisfactory in this test.

IV. DISCUSSION

Public Law 87-637, approved September 4, 1962 states that hydraulic brake fluids sold through interstate commerce must meet certain minimum physical and chemical requirements as set forth in the Federal Register without any time requirement. In addition it would be completely undesirable from the military point of view to have a brake fluid in a vehicle which would fail in storage. Results included in this report show that there is a serious problem and that a comprehensive study must be made to eliminate instability of brake fluid upon aging.

Brake fluids are composed of many combinations of base lubricants, solvents, and inhibitors. Since Federal Brake Fluid Specifications are "Performance" specifications, a wide variety of components are used. The most commonly used base lubricants are either castor oil or polyoxyglycol types. Solvents are usually alcohols, glycols, glycol-ethers, or combinations of these materials. The inhibitor system generally consists of alkaline materials in combination with antioxidant chemicals. Fluids may contain mixtures of base lubricants, many solvents, and many reactive inhibitors. The inhibitors may interreact, deteriorate or become depleted. Some of the situations which may accelerate the breakdown of the inhibitor system are: contact with metals, presence of water, and fluctuating temperatures. However, the fact that it is possible to prepare hydraulic brake fluids which are stable in storage is indicated in the test results. (Tables I and II).

The following studies are in progress or planned:

1. Correlation between brake fluid composition and storage stability.
2. Factors affecting inhibitor breakdown.
3. Development of accelerated test methods for predicting shelf life of brake fluids.

The matter of instability of hydraulic brake fluids upon aging has been brought to the attention of fluid suppliers and the automotive industry through the Society of Automotive Engineers Ad Hoc Committee on Brake Actuating Systems.

V. REFERENCES

1. Authority: AMC Directive, AMC Code 5025.11.802 dated 24 July 1964.
2. Federal Specification VV-H-910a, Hydraulic Fluid, Non-Petroleum Base, Automotive.
3. Public Law 87-637, dated 5 September 1962.
4. Specification 70R1, Society of Automotive Engineers, 485 Lexington Avenue, New York, New York.

Best Available Copy

DISTRIBUTION LIST FOR AMCMS CODE NO. 5025.11.802

<u>Department of Defense</u>	<u>No. of Copies</u>
Defense Documentation Center Cameron Station Alexandria, Virginia 22314	20
<u>Department of the Army - Technical Service</u>	
Commanding General U. S. Army Materiel Command ATTN: AMCRD-RC Washington, D. C. 20315	1
Continental Army Command Department of the Army Fort Monroe, Virginia 23351	3
Commanding Officer U. S. Army Tank-Automotive Center ATTN: Mr. J. P. Jones Mr. V. Pogano Warren, Michigan 48090	1 1
Commanding Officer Frankford Arsenal ATTN: SMUFA 1320 Library Philadelphia, Pa. 19137	1 1
Commanding Officer U.S. Army Materials Research Agency Watertown Arsenal ATTN: Technical Information Center Watertown, Massachusetts 02172	2
Commanding Officer U.S. Army Test Activity Yuma Test Activity Yuma, Arizona 85364	1
Commanding General U.S. Army Weapons Command ATTN: ANSWE-RDR Rock Island, Illinois 61200	2
Commanding Officer U.S. Army Chemical Research & Development Laboratories ATTN: Librarian Edgewood Arsenal, Maryland 21040	1

DISTRIBUTION LIST CONTINUED

	<u>No. of Copies</u>
U.S. Army Engineer R & D Laboratories ATTN: STINFO Branch Fort Belvoir, Virginia 22060	2
Commanding Officer Rock Island Arsenal ATTN: Laboratory 9320 Rock Island, Illinois 61200	1
Commanding Officer U.S. Army Ballistic Research Laboratories ATTN: Mr. W. C. Pless Mr. R. Eichelberger Mr. J. Sperrazza Aberdeen Proving Ground, Maryland 21005	1 1 1
Technical Library Aberdeen Proving Ground, Maryland 21005	2
<u>Department of the Navy</u> c/o Navy Liaison Aberdeen Proving Ground, Maryland 21005	1
Chief, Bureau of Naval Weapons Washington 25, D. C.	1
<u>Other Government Agencies</u> Scientific and Technical Information Facility ATTN: NASA Representative (S-AK/DL) P. O. Box 5700 Bethesda, Maryland 20014	3
Post Office Department ATTN: Mr. Val Russak 12th & Penn Washington D. C. 20260	1
<u>Foreign Address</u> Ministry of Supply Staff British Joint Services Mission 1800 K Street, N. W. Washington 6, D. C.	2
Canadian Army Staff ATTN: GSO-1, A&R Section 2450 Massachusetts Avenue, N. W. Washington 8, D. C.	2

APPENDIX

TABLE I

SERIES I - 2½ YEARS STORAGE IN 5 GALLON STEEL CONTAINERS -
VV-H-910a BRAKE FLUIDS

Fluid No.	Corrosion Test	Stability Test
1	O. K.	O. K.
2	O. K.	O. K.
3	**Aluminum - Pitted	*Aluminum - Pitted
4	O. K.	*Aluminum - Pitted
5	*Aluminum & Brass - Moderate Stain	**Aluminum & Cast Iron - Pitted
6	*Brass - Moderate Stain	**Aluminum & Cast Iron - Pitted
7	*Brass - Moderate Stain	O. K.
8	*Aluminum - Moderate Stain	*Aluminum - Pitted
9	*Aluminum - Moderate Etching	O. K.
10	**Aluminum - Pitted, Brass - Moderate Stain	O. K.
11	*Brass - Moderate Stain	O. K.
12	**Steel - Pitted, Cast Iron - Moderate Stain	O. K.
13	*Brass - Severe Stain	O. K.
14	O. K.	O. K.
15	*Aluminum Moderate Etching	**Aluminum & Cast Iron - Pitted
16	*Aluminum - Pitted	**Aluminum - Pitted
17	O. K.	O. K.
18	O. K.	O. K.
19	O. K.	*Aluminum - Pitted

TABLE 1 - Cont'd.

SERIES 1 - 2½ YEARS STORAGE IN 5 GALLON STEEL CONTAINERS -
VV-H-910a BRAKE FLUIDS

Fluid No.	Corrosion Test	Stability Test
20	O. K.	*Aluminum - Pitted
21	**Aluminum - Pitted	*Aluminum - Pitted
22	**Aluminum - Pitted, Brass - Severe Stain	**Aluminum - Pitted

*Fails to meet minimum VV-H-910a requirements.

**Fails VV-H-910a and SAE 70R1.

TABLE II
Series 2 - 5 Years Storage in Glass Containers
VV-H-910a Brake Fluids

Fluid No.	Corrosion Test	Stability Test
4	0. K.	**Cast Iron - Pitted
5	*Brass - Severe Stain	0. K.
7	*Brass - Severe Stain	*Aluminum - Pitted
9	0. K.	0. K.
10	**Aluminum - Pitted	*Aluminum - Pitted
12	0. K.	0. K.
15	0. K.	0. K.
21	**Steel-Pitted, Brass-Severe Stain	**Aluminum - Pitted

* Fails to meet minimum Specification VV-H-910a Requirements.
 ** Fails VV-H-910a and SAE 70R1.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1 ORIGINATING ACTIVITY (Corporate author) U. S. Army Coating and Chemical Laboratory Aberdeen Proving Ground, Maryland		2a REPORT SECURITY CLASSIFICATION Unclassified
		2b GROUP
3 REPORT TITLE PRELIMINARY STUDIES ON THE STORAGE STABILITY OF BRAKE FLUIDS		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) INVESTIGATION		
5 AUTHOR(S) (Last name, first name, initial) JORDAN, CHARLES B.		
6. REPORT DATE FEBRUARY 1965	7a TOTAL NO OF PAGES 12	7b NO OF REFS 4
8a CONTRACT OR GRANT NO. AMCMS Code No. 5025.11.802	9a. ORIGINATOR'S REPORT NUMBER(S) CCL #176	
b. PROJECT NO. IC024401A108		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		
10 AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from Defense Documentation Center.		
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY U.S. Army Materiel Command Washington, D. C.	
13 ABSTRACT The object of this study was to investigate the stability of corrosion inhibiting systems found in brake fluids approved under Federal Specification VV-H-910a after extended storage of the fluids in steel and glass containers. Corrosion and oxidation stability tests outlined in VV-H-910a were conducted on twenty-two approved fluids after 2½ years storage in 5-gallon steel containers and on eight approved fluids after 5 years storage in 1-gallon glass containers. In all tests conducted there was evidence of inhibitor instability or depletion. Sixteen of the twenty-two fluids stored in cans and five of the eight fluids stored in glass failed to meet minimum requirements of specification VV-H-910a. Nine of the fluids stored in cans and three of the fluids stored in glass also fail the more relaxed requirements of Society of Automotive Engineers Specification, 70R1, which is the controlling specification of the Federal Register.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.